

## BACnet RIB®

June 24, 2016

### Protocol Implementation Conformance Statement

Vendor Name: **Functional Devices, Inc.**  
Product Name: **BACnet RIB**  
Product Model Number: **RIBTW240xB-BC**  
Applications Software Version: **1.1**  
Firmware Revision: **2.04**  
BACnet Protocol Revision: **12**

#### 1. Product Description

The BACnet RIB provides a software-implemented network interface between BACnet client devices and RIB control and monitoring points.

#### 2. BACnet Standardized Device Profile (Annex L)

The BACdoor OEM Client-Server supports the B-ASC profile.

#### 3. BACnet Interoperability Building Blocks Supported (Annex K)

DS-RP-B, DS-RPM-B, DS-WP-B, DS-WPM-B, DM-DDB-B, DM-DOB-B, DM-DCC-B, DB-RD-B

#### 4. Segmentation Capability

Segmentation is not supported.

#### 5. Standard Object Types (See Specification for product to see which are supported on the product)

No dynamic Creation or Deletion supported  
No proprietary object types supported

Standard Object Types Supported:

- **Binary Input**
- **Binary Output**
- **Device**

Optional Properties Supported:

- **Binary Input**
  - Description
  - Reliability
  - Inactive-Text
  - Active-Text
- **Binary Output**

Description  
 Reliability  
 Inactive-Text  
 Active-Text  
 Minimum-On-Time  
 Minimum-Off-Time  
 Status\_Flags

- **Device**  
 Description  
 Max-Master  
 Max-Info-Frames

Writable Properties:

- **Binary Input**  
 Object-Name (32 characters max)  
 Description (64 characters max)  
 Inactive-Text (32 characters max)  
 Active-Text (32 characters max)  
 Polarity
- **Binary Output**  
 Object-Name (32 characters max)  
 Description (64 characters max)  
 Inactive-Text (32 characters max)  
 Active-Text (32 characters max)  
 Polarity  
 Present-Value  
 Relinquish-Default  
 Minimum-On-Time  
 Minimum-Off-Time
- **Device**  
 Object-Identifier  
 Description (64 characters max)  
 APDU-Timeout  
 Number-Of-APDU-Retries  
 Max-Master  
 Object-Name (32 characters max)

### Object Details

DEx	Object_Identifier	default to DE277000	W
	Object_Name	Up to 32 characters	W
	Object_Type	DEVICE	R
	System_Status	OPERATIONAL or NON_OPERATIONAL	R
	Vendor_Name	"Functional Devices, Inc"	R
	Vendor_Identifier	277	R
	Model_Name	"RIBTW240xB-BC" (or similar)	R
	Firmware_Revision	"2.04" (or similar)	R
	Application_Software_Version	"1.1" (or similar)	R
	Description	Up to 64 characters	W
	Protocol_Version	1	R
	Protocol_Revision	12	R
	Protocol_Services_Supported	{readProperty,readPropertyMultiple,writeProperty,writePropertyMultiple,deviceCommunicationControl,who-Has,who-Is, reinitDevice }	R

	Protocol_Object_Types_Supported	{BinaryInput, BinaryOutput, Device }	R
	Object_List	DEx, B11, BO1	R
	Max_APDU_Length_Accepted	480	R
	Segmentation_Supported	NONE	R
	APDU_Timeout	3000 default	W
	Number_Of_APDU_Retries	1 default	W
	Max_Master	127 default	W
	Max_Info_Frames	1	R
	Device_Address_Binding	always empty	R
	Database_Revision	1	R

B11	Object_Identifier	B11	R
	Object_Name	Up to 32 characters	W
	Object_Type	Binary_Input	R
	Present_Value	0 or 1	R
	Description	Up to 64 characters	W
	Status_Flags	Always { 0,0,0,0 }	R
	Event_State	Always NORMAL	R
	Reliability	Always NO_FAULT_DETECTED	R
	Out_Of_Service	Always FALSE	R
	Polarity	NORMAL or REVERSE	W
	Inactive_Text	Up to 32 characters	W
	Active_Text	Up to 32 characters	W

BO1	Object_Identifier	BO1	R
	Object_Name	Up to 32 characters	W
	Object_Type	Binary_Output	R
	Present_Value	0 or 1	W
	Description	Up to 64 characters	W
	Status_Flags	{ 0,0,0,0 } Normal or {0,0,1,0} Overridden	R
	Event_State	Always NORMAL	R
	Reliability	Always NO_FAULT_DETECTED	R
	Out_Of_Service	Always FALSE	R
	Polarity	NORMAL or REVERSE	W
	Inactive_Text	Up to 32 characters	W
	Active_Text	Up to 32 characters	W
	Minimum_Off_Time	0-65535 seconds	W
	Minimum_On_Time	0-65535 seconds	W
	Priority_Array	16 slots (0, 1, NULL)	R
	Relinquish_Default	0 or 1	W

## 6. Data Link Layer Options

- BACnet/IP, (Annex J)
- ISO 8802-3, Ethernet (Clause 7)
- ANSI/ATA 878.1, 2.5 Mb. ARCNET (Clause 8)
- ANSI/ATA 878.1, RS-485 ARCNET (Clause 8), configurable baud rate to 156K
- MS/TP master (Clause 9): 9600, 19200, 38400, 57600, 76800, 115200 baud
- PTP (Clause 10)

## 7. Device Address Binding

Static binding is not supported.

## 8. Networking Options

The RIB is not a router.

Annex H, BACnet Tunneling Router over IP is not supported

BACnet/IP Broadcast Management Device (BBMD) is not supported

## 9. Character Sets Supported

ISO 10646(UTF-8)  IBM/Microsoft DBCS  JIS C 6226  ISO 10646 (UCS4)  ISO 10646 (UCS2)  
 ISO 8859-1

## 10. Network Security Options

The RIB is a non-secure Device